

WOODWISE®

Wood Patch & Full-Trowel Filler General Properties



- Fills cracks, nail holes, gouges and broken edges
- Dries hard
- Accepts stain at rates similar to ordinary wood
- Water miscible
- Water-based product
- Cleans up with water
- Bonds to surface applied to
- Can be sanded easily
- Comes in a variety of wood colors
- Full-Trowel Filler is available in 3 1/2- gallon and 1-gallon containers
- Wood Patch is available in 1-gallon, 1-quart & 14-ounce containers
- Both Wood Patch & Full-Trowel Filler available in 16 different colors
- Environmentally friendly—contains no harsh solvents
- Drying time will vary depending on humidity and airflow

WOOD PATCH

With its higher solid content, Wood Patch is used for large fill areas and for spot filling before and during sanding. Wood Patch can also be thinned and used as a Full-Trowel Filler; simply mix 1-2 cups of water per one gallon of Wood Patch, and trowel floor as directed below.

Instructions for Use:

Remove all dust, oil and wax. Apply with trowel or putty knife. Press into place, building up patch slightly higher than surrounding surface. Deep areas should be filled in layers, allowing sufficient time for each layer to dry. Sand in customary manner. Clean up tools and finished surfaces with water before material dries. Test on small area before using. Always wear a NIOSH/MSHA dust mask when sanding. DO NOT BLEACH.

FULL-TROWEL FILLER

Full-Trowel Filler is thinner, and designed to spread across the surface of the wood floor. It will also fill cracks, small holes and pores of grain in the wood. Excess filler should be removed.

Instructions for Use:

Rough-sand floor, making sure to remove all wax, oils, etc. (Spot-fill larger voids prior to trowel-filling and during dry time.) Prior to final sand, quickly screen floor, vacuum dust, then pour a workable puddle of Full-Trowel Filler on the floor. Trowel-fill entire floor, back and forth across the cracks and voids to ensure deep penetration, removing excess filler as you go. Allow to dry thoroughly before sanding. Test on small area before using. Always wear a NIOSH/MSHA dust mask when sanding. Covers approximately 600 to 1,000 square feet. Clean up tools and finished surfaces with water before product hardens. DO NOT BLEACH.

Design Hardwood Products, Inc.

PMB 118, 16149 Redmond Way ♦ Redmond, Washington 98052

(425) 869-0859 Fax: (425) 881-2704

www.woodwise.com

