



SPC Vinyl Plank Technical Data Sheet

PRODUCT

Product Type:	Rigid Core Stone Polymer Composite
Overall Thickness:	5.3mm
Wear Layer:	20 Mil (0.5mm)
Finish	UV with Ceramic bead
Size:	7" x 48" Standard
Packing:	23.37 sf/Carton, 65 Cartons/Pallet, 18 Pallets/20'
Lbs Carton:	45 Lbs
Installation Type:	Floating / Interlocking
Attached Pad:	1mm IPEX Pad

PERFORMANCE Commercial Grade Luxury Vinyl Plank

Classification	ASTM F <u>3261</u> - Class I, Type B, Grade 1, Class B ASTM F 3261	
Thickness	ASTM F <u>387</u> Nominal \pm 0.008 in.	Pass
Wear Layer	ASTM <u>410</u>	Pass
Size	ASTM <u>2055</u> \pm 0.016 in. per linear foot	Pass
Squareness	ASTM F <u>2055</u> 0.010 in. max	Pass
Residual Indentation	ASTM <u>1914</u> $<$.007	Pass
Dimensional Stability	ASTM <u>2199</u> 0.08% per linear foot	Pass
Chemical Resistance	ASTM F <u>925</u> No Change	Pass
Resistance to Heat	ASTM F <u>1514</u> ∇ E \leq 8	Pass
Resistance to Light	ASTM F <u>1515</u> ∇ E \leq 8	Pass
Static Load	ASTM F <u>970</u> $<$ 0.05mm	Pass
Flame Spread	ASTM E <u>648</u> 0.45 watt/cm ² or more Class I	Pass
Smoke Density	ASTM E <u>662</u> \leq 450 v	Pass
Warranty	25 Year Residential / 10 Year commercial	

SUPPLEMENTARY

Formaldehyde	ASTM <u>D6007</u>	Carb II Compliant
Heavy Metals Content	ASTM <u>F963</u>	Pass
Indoor Sound Transmission IIC	ASTM <u>E492</u> / <u>E989</u>	52
Sound Transmission Class STC	ASTM <u>E90</u> / <u>E413</u>	53

