

## SPC Vinyl Plank Technical Data Sheet

PRODUCT	
Product Type:	Rigid Core Stone Polymer Composite
Overall Thickness:	5.3 mm
Wear Layer:	20mil (0.5 mm)
Finish:	UV With MATT Finish
Size:	7.13" x 48"
Packing:	23.78sqft/ 55 Cartons/Pallet, 22 Pallets/20'
Lbs Carton:	41.65 Lbs
Installation Type:	UNILIN Interlocking
Attached Pad:	1mm IXPE Pad

PERFORMANCE Commercial Grade Luxury Vinyl Plank	TEST METHOD	TOLERANCE	REMARKS by QC Team
Thickness	ASTM <a href="#">F386</a>	± 0.1 MM	Pass
Wear Layer	ASTM <a href="#">F386</a>	± 0.03 MM	Pass
Size	ASTM <a href="#">F3261</a>	± 0.4 MM	Pass
Squareness	ASTM <a href="#">F3261</a>	≤ 0.25 MM	Pass
Residual Indentation	ASTM <a href="#">F1914</a>	≤ 0.18 MM	Pass
Dimensional Stability	ISO 23999	≤ 0.2	Pass
Chemical Resistance	ASTM <a href="#">F925</a>	VISUAL	Pass
Resistance to Heat	ASTM <a href="#">F1514</a>	VISUAL	Pass
Resistance to Light	ASTM <a href="#">F1515</a>	VISUAL	Pass